

Fixture, Dust/Vapor



Fixture, Wet Location, Dust/Vapor, 120-277 Volt, F32T8 Lamp, 2 Lamp, Suggested Lamp 4PL16, 64 Watt Fixture, Minimum Starting Temp 0 Degree Fahrenheit, Maximum Ambient Temperature 104 Fahrenheit, Electronic Ballast, Length 50 Inches, Width 7.63 Inch, Height 4.75 Inch

Grainger Item # : 3YA23
Brand : LITHONIA
Mfr. Model # : DMW 2 32 MVOLT
GEB10IS WWGR

Additional Info

Wet Location Fluorescent Fixtures

- Fiberglass-reinforced polyester housing won't degrade or oxidize
- Completely enclosed and gasketed
- Lamps not included

Dust-Resistant

Rugged fixtures withstand tough environments where dust, dirt, humidity, moisture, or corrosive elements are present. Units are designed to prevent entry of airborne contaminants that can reduce fixture performance. Impact-resistant acrylic diffuser is secured to housing with cam-action latches for a positive seal. UL Listed for wet locations.

Uses : Fabrication and machining areas, welding, grinding, or any no hazardous environment.

Tech Specs

Item : Wet Location Fluorescent Fixtures
Fixture Type : Commercial/Industrial
Lamp Quantity : 2
Lamp Type : F32T8
Lamp Watts : 32
Fixture Wattage : 60
Voltage : 120-277
Lens Type : Impact Resistant Acrylic
Ballast Type : T8 Electronic
Suggested Lamp Item No. : 4PL16
Lamp Included : Lamp Not Included
Ambient Temp. Range (F) : 0 to 104
Length (In.) : 50
Height (In.) : 4.75
Width (In.) : 8.13
Standards : UL Listed



Excellence - Within Your Reach!

P.O. Box: 2980 Safat, 13030 Kuwait
www.fitco.net sales@fitco.net admin@fitco.net
Phone : 22 4066 44 / 5 Fax : 22 4030 55